



Installation: hazardous areas - Zone 1 / 2 (Gases) - Zone 21 / 22 (Dusts)
Classification: Group II - Category 2G 2D



REFERENCE STANDARDS

Directive 2014/34/EU

EXECUTION	⊗ II 2 G Ex d / Exe / Exia IIC Gb ⊗ II 2 D Ex tb IIIC Db
RULES OF COMPLIANCE	EN/IEC 60079-0; EN/IEC 60079-1; EN/IEC 60079-7; EN/IEC 60079-31
EC Type-Examination Certificate	INERIS 09 ATEX 0028X
PROTECTION DEGREE	IP66 or IP66/68
AMBIENT TEMPERATURE	-40°C ÷ +90°C (Rubber rings EPDM-60) -60°C ÷ +180°C (Rubber rings SILICON)
OTHER AVAILABLE CERTIFICATES	IECEX: IECEX INE 11.0017X INMETRO: CEPEL 12.2177X EAC: TC RU C-IT.BH02.B.00587 (-75°C ÷ +180°C) RINA: ELE139017CS004 RUSSIAN MARINE CERTIFICATE (RMRS): 19.02521.280 CCOE-PESO: P405709/1

Mechanical characteristics

Body / cap	OT-58 marine brass (ON) - AISI-316L stainless steel (IX) marine grade copper free aluminium (on project request only)
Finishes	full nickel plating treatment (brass material only)
Rubber rings	EPDM rubber 50-60 shore hardness (standard supply) Silicon rubber 60 shore hardness (on demand only)
O-ring	silicon rubber - 60 shore hardness
Skid washer	nylon 6.0
Chamber for sealing	OT-58 marine brass ("R" version only)

Applications

For steel wire armoured cables (swa) for steel tape armoured cables
Single compression type for indoor and outdoor use
Provided armour clamping using clamping arrangements suitable for all armour wire/braid types
Single compression - under armour and overall of armour cable (inner and outer sealing)
Sealing with proper resin into "chamber of sealing" (on barrier type version "r" only)



On Request Accessories:

- Locknuts, Gaskets, PVC Shrouds, Earthing Tags, Sealing (See DL-NW-PTD-ET bulletin)

Cable gland selection table

CODE (1)	SIZE	ENTRY THREAD SIZE				DIA. UNDER ARMOUR		OUTER SHEATH DIA. max [mm]	HEXAGON Ø [mm]	MATERIAL			
		METRIC (2)	NPT (2)	ISO 228 (2)	min [mm]	max [mm]	(3)			(3)			
PA# PA-R#	00	(16)ISO-M16 (0)3/8"	M	3/8"NPT	N	3/8"	G	4,0	7,0	10,0	24,0	NICKEL PL. BRASS	ON
								7,0	10,0			STAINLESS STEEL	IX
PA# PA-R#	01	ISO-M20	M	1/2"NPT	N	1/2"	G	5,5	8,0	10,0	32,0	NICKEL PL. BRASS	ON
								8,0	10,5			STAINLESS STEEL	IX
PA# PA-R#	02	ISO-M25	M	3/4"NPT	N	3/4"	G	10,5	13,0	14,0	36,0	NICKEL PL. BRASS	ON
								13,0	15,5			STAINLESS STEEL	IX
PA# PA-R#	03	ISO-M32	M	1"NPT	N	1"	G	15,0	18,0	24,0	45,0	NICKEL PL. BRASS	ON
								18,0	21,0			STAINLESS STEEL	IX
PA# PA-R#	04	ISO-M40	M	1 1/4"NPT	N	1 1/4"	G	21,0	24,0	30,0	53,0	NICKEL PL. BRASS	ON
								24,0	27,0			STAINLESS STEEL	IX
PA# PA-R#	05	ISO-M50	M	1 1/2"NPT	N	1 1/2"	G	27,0	30,0	36,0	61,0	NICKEL PL. BRASS	ON
								30,0	33,0			STAINLESS STEEL	IX
PA# PA-R#	06	ISO-M63	M	2"NPT	N	2"	G	33,0	36,0	45,0	71,0	NICKEL PL. BRASS	ON
								36,0	39,0			STAINLESS STEEL	IX
PA# PA-R#	07	ISO-M75	M	2 1/2"NPT	N	2 1/2"	G	42,0	45,0	54,0	84,0	NICKEL PL. BRASS	ON
								45,0	48,0			STAINLESS STEEL	IX
PA# PA-R#	08	ISO-M90	M	3"NPT	N	3"	G	48,0	51,0	68,0	101,0	NICKEL PL. BRASS	ON
								51,0	54,0			STAINLESS STEEL	IX
PA# PA-R#	09	ISO-M100	M	4"NPT	N	4"	G	52,0	56,0	92,0	126,0	NICKEL PL. BRASS	ON
								56,0	59,0			STAINLESS STEEL	IX

CABLE GLAND ORDERING EXAMPLES

PA#	01	M	ON	= PA#01MON	(NON-BARRIER CABLE GLAND NICKEL PLATED BRASS ISO-M20 THR.)
PA#	03	N	IX	= PA#03NIX	(NON-BARRIER CABLE GLAND STAINLESS STEEL 1"NPT THR.)

LEGEND

(1)	CABLE GLAND TYPE/MODEL	PA# = NON-BARRIER CABLE GLAND - PA-R# = BARRIER CABLE GLAND
(2)	THREADING	M = ISO METRIC pitch 1,5mm - N = NPT (ANSI/ASME B1.20.1) - G = ISO-228
(3)	CABLE GLAND MATERIAL	ON = NICKEL PLATED MARINE BRASS - IX = AISI-316L STAINLESS STEEL

PA DIMENSIONAL

1	BODY
2-3-4	INNER SEALING RING FOR ARMOURED CABLE
5	ARMOUR CLAMPING CONE
6	ARMOUR CLAMPING RING FOR ARMOURED CABLE
7	ANTI RUBBING WASHER
8	GLAND NUT
9	O-RING (ONLY FOR METRICAL)
10	*CHAMBER FOR SEALING ("R" VERSION ONLY)

* Chamber will be filled with sealing when cable gland is completely assembled.

REMARK:

Due to the development of the national and international specifications and of the technology, the above technical characteristics showed on this bulletin can be considered as binding on our confirmation only.